

# レディーミクストコンクリート標準配合表(サンプル)

[ ]

使用材料	生産者又は産地	品名	密度	アルカリ反応性による区分	粒の大きさの範囲	粗粒率又は実積率
	使用材料欄					

呼び強度 配合強度 (N/m <sup>3</sup> )	W/C (%)	スラン 又は フロー (cm)	S/a (%)	単位量 (kg/m <sup>3</sup> )				
				水 (W)	セメント (C)	砕砂 (S1)	山砂 (S2)	粗骨材 (G)
18		8						
		10						
		12						
		15						
		18						
21		8						
		10						
		12						
		15						
		18						
24		8						
		10						
		12						
		15						
		18						
27		8						
		10						
		12						
		15						
		18						
30		8						
		10						
		12						
		15						
		18						
33		8						
		10						
		12						
		15						
		18						
36		8						
		10						
		12						
		15						
		18						
40		8						
		10						
		12						
		15						
		18						

呼び強度 配合強度 (N/m <sup>3</sup> )	W/C (%)	スラン 又は フロー (cm)	S/a (%)	単位量 (kg/m <sup>3</sup> )				
				水 (W)	セメント (C)	川砂 (S1)	山砂 (S2)	粗骨材 (G)
18		5						
		8						
		10						
		12						
		15						
21		5						
		8						
		10						
		12						
		15						
24		5						
		8						
		10						
		12						
		15						
27		5						
		8						
		10						
		12						
		15						
30		5						
		8						
		10						
		12						
		15						

4.5	2.5							
	6.5							

4.5	2.5							
	6.5							

北兵庫生コンクリート(株) 豊岡工場

兵庫県豊岡市庄境958-1  
 TEL 0796-22-7145  
 FAX 0796-24-0706